

KABLO KESİTLERİNE GÖRE MUHTELİF GÜÇLERİN BELİRLİ GERİLİM DÜŞÜMÜNDE TAŞINABİLECEĞİ EN UZUN MESAFELER (3-380V Trifaze)

Güç kW	Akım Şiddeti A	Cos Ø	KESİT mm ²															
			1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	
2,5	5	0.82	240	400	640													
3	6		200	330	535	800												
3,5	7		170	285	455	685												
4	8		150	250	400	600	1000											
4,5	9		135	223	353	530	890											
5	10		120	200	320	480	800											
6	12		100	166	265	400	670	1070										
7	14		85	142	225	340	570	920										
8	16		75	125	200	300	500	800										
9	18		66	110	175	265	445	725	1120									
10	19	0.82	100	160	240	400	640	1000										
12	23		82	133	200	335	535	835	1170									
14	27		75	113	170	285	460	720	1050									
16	31			100	150	250	400	630	880									
18	35			88	130	220	355	560	780									
20	37				120	200	320	500	700	1000								
25	46				95	160	255	400	560	800								
30	55					130	215	335	470	670								
35	65					115	189	285	400	570	805							
40	72					100	160	250	350	500	705							
45	83						140	220	310	445	625	850						
50	93							200	280	400	560	770						
60	107								160	220	335	470	635	800				
70	125										285	400	550	690				
80	143										250	350	480	600	755			
90	160										220	310	425	535	670			
100	180										200	280	380	480	600	740		
110	197	0.85										255	340	440	550	675		
130	232											228	290	370	465	570		
150	268												250	320	400	495	640	
180	320													265	335	410	535	
200	350														300	370	480	
250	405															295	385	
300	500																310	